

APPLICATION

Directly buried or installed in ducts for 600 volt secondary distribution.

PRODUCT FEATURES

- Concentric stranded or compressed 1350-H19 aluminum conductor, crosslinked polyethylene insulation. Insulated conductors surface printed, neutral, triple yellow striped or solid yellow. Black neutrals may be specified if desired.

STANDARDS

- UL Standard 854 for Type USE-2, ASTM B-230, B-231 and
- ICEA S-105-692, Federal Specification JC-30B NEC

600V SECONDARY UD - TRIPLEX

600 Volt Triplex

Code Word	Phase Conductors			Neutral Conductor			Single Phase Conductor (in)	Outside Diameter (in)	Weight per 1000 ft. (lbs)	Ampacity	
	Size AWG	Strand	Insulation Thickness (MLS)	Size AWG	Strand	Insulation Thickness (MLS)				Direct Burial	In Duct
Erksine	6	7/w	60	6	7/w	60	.299	.646	143	95	70
Vassar	4	7/w	60	4	7/w	60	.345	.754	203	125	90
Stephens	2	7/w	60	4	7/w	60	.403	.842	264	165	120
Ramapo	2	7/w	60	2	7/w	60	.403	.874	294	165	120
Brenau	1/0	19/w	80	2	7/w	60	.522	1.064	408	215	160
Bergen	1/0	19/w	80	1/0	19/w	80	.522	1.133	465	215	160
Converse	2/0	19/w	80	1	19/w	80	.566	1.174	502	245	180
Hunter	2/0	19/w	80	2/0	19/w	80	.566	1.228	560	245	180
Hollins	3/0	19/w	80	1/0	19/w	80	.616	1.276	606	280	205
Sweetbriar	4/0	19/w	80	2/0	19/w	80	.672	1.389	739	315	240
Monmouth	4/0	19/w	80	4/0	19/w	80	.672	1.457	828	315	240
Pratt	250	37/w	95	3/0	19/w	80	.748	1.538	893	345	265
Wesleyan	350	37/w	95	4/0	19/w	80	.851	1.736	1166	415	320
Rider	500	37/w	95	350	37/w	95	.979	2.035	1663	495	395
Fairfield	750	61/w	110	500	37/w	95	1.118	2.860	2304	615	525

Ampacity: 90°C conductor temperature, 20°C ambient, RHO 90, 100% load factor for three conductor triplex with neutral carrying only unbalanced load.

All Yellow Extruded Stripe, cable is XLP insulation.

* To determine correct ampacity by conductor size, please consult the National Electric Code, latest edition.

The above data are approximate and subject to normal manufacturing tolerances.