

APPLICATION

Type SOOW Non-UL is designed for use with industrial equipment, battery chargers, portable lights and power extensions. Non-UL Type SOOW is sunlight, water, oil and weather resistant and suitable for outdoor applications.

CONSTRUCTION

- Oil and Water Resistant
- Non-Marking Jacket, Lightweight & Very Flexible at Low Temp.

CONSTRUCTION

- CONDUCTOR: 8 AWG-2 AWG Bare Copper Stranded
- INSULATION: EPDM
- COLOR CODE: See Color Chart Below
- JACKET: CPE
- COLOR: Black
- TEMPERATURE RANGE: -40°C to 90°C

STANDARDS

- INDUSTRY APPROVALS: ICEA where applicable, MSHA listed, passes MSHA flame test (P-136-MSHA), Water, Oil, Weather and Sunlight Resistant, ROHS.

600V RUBBER TYPE SOOW BLACK (NON-UL) COLOR CODE CHART

SOOW NON-UL

Number of Conductors	Color
2	Black, White
3	Black, White, Green
4	Black, White, Red, Green
5	Black, White, Red, Orange, Green

All dimensions and weights are subject to industry standards and tolerance unless otherwise noted.

600V RUBBER TYPE SOOW BLACK (NON-UL)

SOOW NON-UL

Conductor (AWG)	Conductor Stranding (#/AWG)	Nominal Insulation Thickness (in)	Nominal Jacket Thickness (in)	Nominal Overall Diameter (in)	Conductor Concentricity Min.	Filler	Wrapping	Weight per 1000 ft. (lbs)
8/2	119 X.0113	0.050	NA	0.680±0.047	65%	Rubber strip	Non-woven	273
8/3	119 X.0113	0.050	NA	0.719±0.047	65%	Rubber strip	Non-woven	300
8/4	119 X.0113	0.050	NA	0.786±0.047	65%	Rubber strip	Non-woven	441
8/5	119 X.0113	0.050	NA	0.857±0.047	65%	Rubber strip	Non-woven	503
6/2	119 X.0142	0.050	NA	0.755±0.047	65%	Rubber strip	Non-woven	350
6/3	119 X.0142	0.050	NA	0.798±0.047	65%	Rubber strip	Non-woven	465
6/4	119 X.0142	0.050	NA	0.873±0.047	65%	Rubber strip	Non-woven	626
6/5	119 X.0142	0.050	NA	0.971±0.047	65%	Rubber strip	Non-woven	777
4/2	119 X 26	0.050	NA	0.841±0.047	65%	Rubber strip	Non-woven	478
4/3	119 X 26	0.050	NA	0.893±0.047	65%	Rubber strip	Non-woven	664
4/4	119 X 26	0.050	NA	0.999±0.047	65%	Rubber strip	Non-woven	869
4/5	119 X 26	0.050	NA	1.093±0.047	65%	Rubber strip	Non-woven	1030
2/2	133 X.0211	0.050	NA	0.992±0.047	65%	Rubber strip	Non-woven	710
2/3	133 X.0211	0.050	NA	1.091±0.047	65%	Rubber strip	Non-woven	1065
2/4	133 X.0211	0.050	NA	1.181±0.047	65%	Rubber strip	Non-woven	1285
2/5	133 X.0211	0.050	NA	1.331±0.047	65%	Rubber strip	Non-woven	1602

All dimensions and weights are subject to industry standards and tolerance unless otherwise noted.

Specifications may be revised without prior notice. Contact Electro Cable to verify current availability and lead times.